



FAKTOR GmbH
Spinnereinsel 3D
D-83059 Kolbermoor
Tel +49 8031 2080023
Fax +49 8071 93122
www.faktor.de

CL4Y Ladegeräte

Specification of Battery Charger

Model Number: EJ21610LL

LITHIUM BATTERY CHARGER

(Aluminum enclosure)



Doc No: SPE-BC-0143

Prepared	Checked	Approved
Sara	Jess	John

1. General

Battery Charger EJ21610LL, 340×220×116mm aluminum shell charger with reverse polarity protection function..

2. Main product specification

Max. output power	Input voltage	Output voltage	Output current	Combined regulation
3000W	220Vac	219V+/-0.2Vdc	10A	+/-0.2

3. Environmental condition

No.	Item	Technical specification	Remark
1	Humidity	5~95%	With package
2	Altitude	≤3000m	Work normally

4. Electrical characteristics

4.1 Input characteristic

No.	Item	Technical specification	Remark
1	Rated input voltage	220Vac	
2	Input voltage range	189~ 264Vac	
3	AC input voltage frequency	50~60 Hz	

4.2 Output characteristic or charge stages

No.	Item	Technical specification	Remark
1	CC (constant current)	≤219Vdc, 10A	
2	CV (constant voltage)	219Vdc, 10A ↓	
3	Cut off	219V,0.5A	5%CC
4	Power efficiency	≥85%	Vin=110Vac, rated load

4.3 Protection characteristics

No.	Item	Technical specification	Remark
1	Software over voltage protection	The charger output voltage does not exceed set the maximum charging voltage of the battery.	
2	Thermal	Aluminum shell the inside temperature > 65 °C , Automatic	

	protection	Shutdown Transformer temperature > 110°C, Automatic Shutdown	
3	Current limiting protection	The charger output current does not exceed a set battery charge current.	At CC mode
4	Short circuit protection	Short circuit protection should be automatically recovery after remove the condition.	
5	Reverse polarity protection	When output wires are reversely connected to the battery the charger will not operate and will work normally when DC wires are correctly connected.	

4.4 Charging indicator

No.	Item	Status	Remark
1	Power on	LED1: Red LED2: Green	
2	Charging	LED1: Red LED2: Red	
3	Fully charged	LED1: Red LED2: Green	
4	Charging Voltage Display	Yes	
5	Charging Current Display	Yes	

5. Safety & EMC

No.	Item	Standard (or test condition)	Remark
1	Electric strength test Input-output	1500Vac/1min ≤ 10mA	No breakdown
2	Isolation resistance Input-ground Output-ground	≥ 10Mohm@500Vdc	
		≥ 10Mohm@500Vdc	
3	Leakage current	< 3.5mA	
4	Safety	<input type="checkbox"/> CE <input type="checkbox"/> RoHs <input type="checkbox"/> GS <input type="checkbox"/> UL <input type="checkbox"/> CCC <input type="checkbox"/> SAA <input type="checkbox"/> PSE <input type="checkbox"/> KC	
5	EMC	EN55022:1998+A1:2000+A2:2003 EN55024:1998+A1:2001+A2:2003 (EN61000-4-2:1995+A1:1998+A2:2001) EN61000-4-3:2002 EN6100-4-4:1995+A1:2000+A2:2001 EN61000-4-5:1995+A1:2000 EN61000-4-6:2001 EN61000-4-11:2001)	
6	LVD	EN60335-1:2002+EN60335-2-29:2002	

Remark: Discrimination A- Function OK under technical requirement range;

Discrimination R- Physical damage or failure of equipment are not allowed, but damage of protection device (fuse) caused by interference signal of outside is allowed, and the whole equipment can work normally after replacement of protection device and reset of running parameter

6. Environmental testing requirements

No.	Item	Technical specification	Remark
1	High environmental temperature ambient operating	+40°C	Features OK
2	Low environmental temperature ambient operating	-10°C	Features OK
3	High temperature storage	+70°C	Work normally after recovery under normal temperature for 2 hours
4	Low temperature storage	-40°C	Work normally after recovery under normal temperature for 2 hours
5	Random vibration	20Hz to 500Hz Acceleration 0.49	
6	Repetitive shock	10Hz to 60Hz Amplitude 0.38	
7	Thermal shock	-35°C to 75°C, <3min transition, 2.5hours dwell, 200cycle	
8	Drop test	BS EN60068-2-32:1993 TEST ED: free fall appendix B	

7. Mechanical characteristic

Shell material: Aluminum

Outline dimension: L*W*H=340×220×116mm

Input socket: meets IEC standard

AC wires: 1.5m length

DC wire: 1.5m length

Net Weight: 8.5Kg

8. Package, transportation & storage

8.1 Package:

There is product name, model, name of manufacturer, safety approval, serial number, User Manual and packing list in the package box.

8.2 Transportation:

Suit for transportation by truck, the products should be Placed in cool dry place, and loaded and unloaded carefully.

8.3 Storage:

Products should be stored in package box when it is not used. And Warehouse extreme temperatures should be

-40 ~ 70 °C, the normal temperature -20 ~ 50 °C, and relative humidity is 5~95%. In the warehouse, there should not be harmful gas, inflammable, explosive products, and corrosive chemical products, and strong mechanical vibration, shock and strong magnetic field affection. The package box should be above ground at least 20cm height, and 50cm away from wall, thermal source, and vent. Under this requirement, product has 2 years of storage period, and should be rechecked when over 2 years.

9. Reliability requirements

MTBF (standard, environmental temperature, load requirement) $\geq 50K$ hours;

testing condition: 25°C, full load, testing proved value.

10. Charging Curve

