

Faktor.
technische Teile

FAKTOR GmbH
Spinnereinsel 3D
D-83059 Kolbermoor
Tel +49 8031 2080023
Fax +49 8071 93122
www.faktor.de

CL4Y Ladegeräte

Specification of Battery Charger

Model Number: EJ2412AL

24V /12A Lithium BATTERY CHARGER

(Aluminium Case)



Doc No: SPE-BC-0112

Prepared	Checked	Approved
Sara	Jess	John

1. General

Battery Charger EJ2412AL, 170×90×63mm can work normally under 29.2Vdc/10A and with reverse polarity protection.

2. Main product specification

Max. output power	Input voltage	Output voltage	Output current	Combined regulation
360W	230Vac	29.2V±0.2Vdc	12A	±0.2V

3. Environmental condition

No.	Item	Technical specification	Remark
1	Humidity	5~95%	With package
2	Altitude	≤3000m	Work normally

4. Electrical characteristics

4.1 Input characteristic

No.	Item	Technical specification	Remark
1	Rated input voltage	230Vac	EU
2	Input voltage range	180~ 264Vac	
3	AC input voltage frequency	50~60 Hz	

4.2 Output characteristic or charge stages:

No.	Item	Technical specification	Remark
1	CC (constant current)	≤29.2 Vdc, 12A	
2	CV (constant voltage)	29.2 Vdc, 12A↓	CV=max.voltage
3	Cut off	29.2 Vdc, 0.5A	5%CC
4	Power efficiency	≥90%	Vin=230Vac, rated load

4.3 Protection characteristics

No.	Item	Technical specification	Remark
-----	------	-------------------------	--------

1	Over voltage protection		
2	Software over voltage protection	The charger software limits the maximum output voltage to a level suitable for the connected battery system	
3	Thermal protection	N/A	
4	Current limiting protection		At CC mode
5	Short circuit protection	Short circuit protection should be automatically recovery after remove the condition	
6	Reverse polarity protection	When output wires are reversely connected to the battery the charger will not operate and will work normally when DC wires are correctly connected.	

4.4 Charging indicator

No.	Item	Status	Remark
1	Power on	LED1: Red	
2	Charging	LED2: Red	
3	Fully charged	LED2: Green	
4	Charging Voltage Display	NO	
5	Charging Current Display	NO	

5. Safety & EMC

No.	Item	Standard (or test condition)	Remark
1	Electric strength test	Input-output 1500Vac/10mA/1min	No breakdown
2	Isolation resistance	Input-ground $\geq 10\text{Mohm}@500\text{Vdc}$	
		Output-ground $\geq 10\text{Mohm}@500\text{Vdc}$	
3	Leakage current	$< 3.5\text{mA}$	Vin=264Vac
4	Safety	CE / UL compliant	
5	EMC	EN55022:1998+A1:2000+A2:2003 EN55024:1998+A1:2001+A2:2003 (EN61000-4-2:1995+A1:1998+A2:2001) EN61000-4-3:2002 EN6100-4-4:1995+A1:2000+A2:2001 EN61000-4-5:1995+A1:2000 EN61000-4-6:2001 EN61000-4-11:2001)	
6	LVD	EN60335-1:2002+EN60335-2-29:2002	

Remark: Discrimination A- Function OK under technical requirement range;

Discrimination B- Function temporarily debasement without reposition and halt is allowed;

Discrimination R- Physical damage or failure of equipment are not allowed, but damage of protection device (fuse) caused by interference signal of outside is allowed, and the whole equipment can work normally after replacement of protection device and reset of running parameter

6. Environmental testing requirements

No	Item	Technical specification	Remark
1	High temperature ambient operating	+40°C	Features ok
2	Low temperature ambient operating	-10°C	Features ok
3	High temperature storage	+70°C	Work normally after recovery under normal temperature for 2hours
4	Low temperature storage	-40°C	Work normally after recovery under normal temperature for 2hours
5	Random vibration	20Hz to 2000Hz 3Grms 20hours per axis	
6	Repetitive shock	40g peak 3 orthogonal axes, 3+ and 3- in each axis, 11ms pulse width	
7	Thermal shock	-35°C to 75°C, < 3min transition, 2.5hours dwell, 200cycle	
8	Drop test	BS EN60068-2-32:1993 TEST ED: free fall appendix B	

7. Mechanical characteristics

Outline dimension: L*W*H=170×90×63mm

Input socket: meets IEC standard

AC wire: 1.5m length

DC wire: 1.5m length

Net Weight: 1.2Kg

8. Package, transportation & storage

8.1 Package:

There is product name, model, name of manufacturer, safety approval, serial number, User Manual and packing list in the package box.

8.2 Transportation:

Suit for transportation by truck, the products should be shielded by tent from sunshine, and loaded and unloaded carefully.

8.3 Storage:

Products should be stored in package box when it is not used. And warehouse temperature should be $-40\sim 70^{\circ}\text{C}$, and relative humidity is 5~95%. In the warehouse, there should not be harmful gas, inflammable, explosive products, and corrosive chemical products, and strong mechanical vibration, shock and strong magnetic field affection. The package box should be above ground at least 20cm height, and 50cm away from wall, thermal source, and vent. Under this requirement, product has 2years of storage period, and should be rechecked when over 2years.

9. Reliability requirements

MTBF(standard, environmental temperature, load requirement) $\geq 50\text{K}$ hours; testing condition: 25°C , full load, testing proved value.

10. Charger wiring

10.1 A spark often on first connection of the charge to the battery terminals due to charging the internal output capacitors, this is normal and should not lead to undue concern, care should be taken to ensure the battery vent caps are closed and there are no flammable object in the vicinity of where the connection will be made

10.2 The charger has been calibrated to take account of the voltage drop in the DC output cables during operation, to prevent the possibility of over or under charging of the battery it is recommended the DC output cable are connected directly to the battery without modification. We are able to customize cable length and connections for volume customers with specific requirements.

11. Charging Curve

