




Technical manual

ELERIX SOLAR PANEL

Mono Crystalline Solar Module
320Wp Black



www.elerix.com

[PRODUCT WEBPAGE >](#)

EXS-320-FB







ELERIX SOLAR PANEL

Mono Crystalline Solar Module
320Wp black




ELERIX Mono Crystalline Solar Module 320Wp Black


Key Features


-  Excellent module efficiency 20.88%
-  IP68 junction box for long-term weather endurance
-  Heavy snow load up to 5400 Pa, wind load up to 3600 Pa
-  PID: Selected material and stringent quality system ensure PID free
-  Applicable to harsh environment of deserts, farmlands and seashores
-  Much lower risk of Hot Spot

Warranty

Linear power output warranty

-  30 years
 - ▶ 12 years minimum 92% power output
 - ▶ 30 years minimum 83% power output

-  12 years
 - Product warranty on materials and workmanship
 - According to the applicable ELERIX Limited Warranty Statement





Certification



ELERIX SOLAR PANEL



Mono Crystalline Solar Module
320Wp black





ELERIX SOLAR PANEL



Mono Crystalline Solar Module
320Wp black

IV CURVE



Electrical Specification	???kód_produkту???
Maximum Power (Pmax)	320 W
Module Efficiency	19.67 %
Open Circuit Voltage (Voc)	40.90 V
Short Circuit Current (Isc)	10.15 A
Maximum Power Voltage (Vmp)	33.40 V
Maximum Power Current (Imp)	9.59 A
Maximum System Voltage	ICE 1500 VDC/UL 1500 (VDC)
Maximum Series Fuse Rating	20

ELERIX SOLAR PANEL



Mono Crystalline Solar Module
320Wp black

Electrical DATA@NOCT	???kód_produkту???
Pmax [W]	239
Vm [V]	31.40
Imp [A]	7.62
Voc [V]	37.80
Isc [A]	8.44

NOCT: Irradiance: 800W/m², Ambient Temperature: 20°C, Air Mass: 1.5, Wind Speed: 1m/s

Mechanical Specification	
Solar Cell Type	Mono Cr stalline Solar Module 156x156 mm
Number of Cells	60 pcs (6x10)
Module Size	1665*1002*35 mm
Weight	18.0 kg
Glass	3.2 mm tempered glass
Back Sheet	Black
Frame	Anodized aluminium alloy frame, silver or black
Junction Box	IP68
Connector	MC4 Compatible
Wind/Snow Load	3600pa/5400pa

ELERIX SOLAR PANEL

Mono Crystalline Solar Module
320Wp black



Packaging Configuration

Modules per box	30 pieces
Number per 20GP	360 pieces
Modules per 40' HQ	910 pieces

Temperature Characteristic

NMOT (Nominal Module Operating Temperature)	45°C (±2°C)
Temperature Coefficient of P _{MAX}	- 0.39%/°C
Temperature Coefficient of U _{oc}	- 0.30%/°C
Temperature Coefficient of I _{sc}	0.05%/°C

Maximum Ratings

Operational Temperature	-40 to +85°C
Maximum System Voltage	1500V DC (IEC) 1500 DC (UL)
Max Series Fuse Rating	20 A
Snow Load	5400 Pa (3600 Pa)
Wind Load	3600 Pa (1600 Pa)

*design load with safety factor 1.5 (DO NOT connect Fuse in Combiner Box with two or more strings in parallel connection)

Are you interested in more details?
Visit our online presentation.

[PRODUCT WEBPAGE >](#)